

**Canon**

***LASER CLASS 710***

**NETWORKABLE MULTIFUNCTION FACSIMILE**



# LASER CLASS® 710

## Specifications

<b>Type:</b>	Desktop Transceiver	<b>Energy Saver:</b>	Approx. 5W	<b>Convenience:</b>	Auto Receive Reduction (70%~100%)
<b>Applicable Line:</b>	Public Switched Telephone Network	<b>Dimensions (H x W x D):</b>	18-1/8" x 19-3/4" x 19-3/4" (Excluding Handset Option) (458.9mm X 498.7mm X 498.7mm)	Speaker Monitor	
<b>Compatibility:</b>	G3	<b>Weight (Excluding Handset Option):</b>	51 lb. (23.2kg)	Dual Access	
<b>Automatic Document Feeder:</b>	Up to 70 Letter-sized Sheets* Up to 30 Legal-sized Sheets* Up to 30 Ledger-sized Sheets*	<b>Environmental Conditions</b>		Transmission Reservation: Up to 70 Reservations	
<b>Scanning Method:</b>	Contact Image Sensor	<b>Temperature:</b>	50°F - 90.5°F (10°C - 32.5°C)	LCD (Liquid Crystal Display): 20 digits x 2 lines	
<b>Document Sizes:</b>	Maximum: 11" x 39.4" (279mm x 1000mm) Minimum: 5.8" x 5" (148mm x 128mm)	<b>Humidity:</b>	20% - 80% RH	Department Access Code: Up to 99 Codes	
<b>Effective Scanning Width:</b>	10" (254mm)	<b>Dialing:</b>	Automatic Dialing	Local Copy Function: Multiple Copy up to 99 Pages	
<b>InstaScan:</b>	Approx. 1.1 Sec./Page (LTR, Standard Mode) Approx. 35 Scans/Min. (LTR, Standard Mode)	One-touch Speed-dialing: 72 Locations		Program Buttons: Up to 72	
<b>Data Compression System:</b>	MH, MR, MMR, JBIG**	Coded Speed-dialing: 128 Locations		Memory Lock Reception	
<b>Modem Speed:</b>	33.6/31.2/28.8/26.4/24/21.6/19.2/ 16.8/14.4/12/9.6/7.2/4.8/2.4 Kbps Automatic Fallback	Group Dialing: 199 Groups (Each Group Can Accommodate Up to 199 Locations)		Battery Backup: Up to 12 Hours	
<b>Transmission Speed:</b>	Approx. 3 Sec./Page*** (V.34/33.6 Kbps + JBIG)	Maximum Dial Digits: 120		Rx Document Multiple Printout Up to 99 Pages	
<b>Printing Method:</b>	Laser Dry Electrostatic Transfer	On-hook Dialing		Rx Page Footer	
<b>Printing Speed:</b>	Approx. 19 Pages/Min. (LTR)	Manual Dialing with 10-button Keypad		Transfer	
<b>Halftone:</b>	256 Shades of Gray	Automatic Redialing		Page Retransmission	
<b>TX/RX Resolution:</b>	Horizontal Vertical	Redial Times 1 to 10 Times/Interval 2 to 99 Min.		<b>Report/Reference:</b>	
<b>Ultra Fine Mode:</b>	406 pels/in. x 391 lines/in. (16 pels/mm x 15.4 lines/mm)	Manual Redialing		Activity Report (Up to 40 Transactions)	
<b>Super Fine Mode:</b>	203 pels/in. x 391 lines/in. (8 pels/mm x 15.4 lines/mm)	Dial Search		Non-delivery Report	
<b>Fine Mode:</b>	203 pels/in. x 196 lines/in. (8 pels/mm x 7.7 lines/mm)	Clear Key		Management Report	
<b>Standard Mode:</b>	203 pels/in. x 98 lines/in. (8 pels/mm x 3.85 lines/mm)	Copy Key		List of Phone Numbers for One-touch and Coded Speed-dialing	
<b>Effective Recording Width:</b>	8.2" (210mm)	Tone Dialing Key		List of Transaction Schedule	
<b>Recording Paper Supply:</b>	600 Sheets: 2 x 250-sheet Cassette, 100-sheet MP Tray	Pause Key		User Data List	
<b>Receiving Paper Tray:</b>	Face-up 250 Sheets	Energy Saver Key		File Reference	
<b>Recording Paper Size:</b>	Letter/Legal/A4	<b>Networking:</b>	Delayed Transmission: Up to 210 Destinations and Up to 70 Reservations	TTI (Transmitter Terminal Identification)	
<b>Enhanced Imaging Quality:</b>	UHQ™ (Ultra High Quality)	Memory Polling Transmission		TTI Selector: Up to 99 Identifications	
<b>Enhanced Printing Quality:</b>	Smoothing for Incoming Faxes	Polling Reception		RTI (Remote Terminal Identification)	
<b>Printing Resolution:</b>	1200 dpi at 19 ppm	Multi-polling: Up to 210 Locations		<b>Options:</b>	
<b>Printer Cartridge:</b>	FX7 Cartridge	Delayed Polling: Up to 200 Locations		33.6 Kbps Dual Line	
<b>Cartridge Yield:</b>	Approx. 4,500 Pages*	Up to 5 Designated Times per Speed-dial		Printer Kit/Network Kit/Printer Memory (Available in February 2003)	
<b>Power Consumption Standby:</b>	Approx. 13W	Sequential Broadcast: Up to 210 Locations (200 preprogrammed Speed-dials)		500-sheet, Letter-sized Cassette	
		Relay Broadcast: Up to 200 Locations		Verification Stamp/Ink Refill	
		Relay Boxes: Up to 50		Telephone Handset Kit 8	
		Delayed Relay Broadcast: Up to 5 Designated Times per Speed-dial		Pedestal (H x W x D) 17-3/4" x 19" x 17-1/2" (450mm x 482mm x 444mm)	
		Relay Broadcast Command/Delayed Relay Broadcast Command Transmission to Confidential Mailbox			
		Confidential Mailbox: Up to 50 Boxes			
		Memory Transmission/Reception: (8MB) Total 512 Pages, with Options up to 1,500 Pages *			
		Receiving Restriction			
		Password and Sub-address (ITU-T STD)			
		Confidential Mailbox			
		Polling			
		Memory Retransmission			

\*Temperature: 15 - 27.5°C; Humidity: 20 - 80% RH;  
Paper Weight: 20 lb.; Paper Thickness: less than 120µm  
\*\* Actual compression ratio may vary with image  
\*\*\* Approximate 3-second-per-page fax transmission time based on ITU-T No. 1 Chart (JBIG, Standard Mode) at 33.6 Kbps modem speed when transmitting to another V.34 machine. The Public Switched Telephone Network (PSTN) currently supports 28.8 Kbps modem speeds or lower, depending on telephone line conditions.  
† Based on 4% original, 5% coverage.  
‡ Based on ITU-T No. 1 Chart (Standard Mode).  
I-fax, Network Faxing, Network Printing Available at a later date.

As an ENERGY STAR® Partner, Canon U.S.A., Inc. has determined that this product meets the ENERGY STAR® guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR certification are registered U.S. trademarks. Canon and LASER CLASS are registered trademarks, and UHQ, the SUPER G3 logo, Canon Know How, and the GENUINE logo are trademarks of Canon Inc. IMAGEANYWARE is a service mark of Canon U.S.A., Inc. All other terms and product names may be trademarks or registered trademarks of their respective owners, and are hereby acknowledged.

Specifications subject to change without notice.

0033W734

0902-LC710-25M



PRINTED ON RECYCLED PAPER IN THE U.S.A.



**Canon** KNOW HOW™

1-800-OK-CANON  
www.usa.canon.com

Canon U.S.A., Inc.  
One Canon Plaza  
Lake Success, NY 11042